



EPK -1000 PATCH KIT

2- COMPONENT CLEAR PATCHING KIT, BONDS, FILL & SEAL CRACKS, CONTROL JOINTS AND LOW SPOTS IN CONCRETE FLOORS. THIS PRODUCT IS RECOMMENDED FOR YOUR EPOXY FLOOR APPLICATIONS



DIRECTIONS: MIXING RATIO: 2 to 1. Pour contents of Part "B" completely into Part "A" pail while mixing with drill mixer, be sure to wipe all sides and bottom of mixture to thoroughly, mix contents together for 3 minutes. Then apply to joints or cracks **IMMEDIATELY**, leaving a very thin coating on the surface, Any high build ups will be visible when you apply top coat. Some sanding is required.

WARNING: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE SKIN AND EYE IRRITATIONS. EYE PROTECTION AND RUBBER GLOVES ARE ALWAYS RECOMMENDED WHEN HANDLING THIS PRODUCT.

FIRST AID: IN CASE OF EYE OR SKIN CONTACT, FLUSH WITH LARGE AMOUNTS OF WATER FOR MINIMUM OF 15 MINUTES, IF IRRITATION PERSISTS, SEE PHYSICIAN. IN CASE OF ACCIDENTAL INGESTION, DO NOT INDUCE VOMITING, DRINK LARGE QUANTITIES OF WATER TO DILUTE PRODUCT. SEEK MEDICAL ATTENTION AT ONCE. Read MSDS thoroughly before using

DISPOSAL: PRECAUTIONS ON THIS LABEL ALSO APPLY TO EMPTY CONTAINERS. RINSE EMPTY CONTAINER AND DISPOSE OF IN ACCORDANCE WITH COMPANY POLICY AND GOVERNMENT REGULATIONS.

KEEP OUT OF REACH OF CHILDREN. KEEP FROM FREEZING. FOR INDUSTRIAL USE ONLY



PERFORMANCE INDUSTRIES, LLC

169 NORTH GRATIOT AVE.

MT. CLEMENS, MI 48043

PH 1 800 841 5580

CONTENTS: 1 GAL. 3.78 L

CHEMICAL EMERGENCY CONTACT:

CHEM TREC 800 424 9300

Refer to: # 627513

MFG. and Packaged for Performance Industries by EPOXY-COAT INC.

EPK - 1000 PATCH KIT	
HEALTH	2
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	2